







SYNRange PRO

Ideal turf product for large indoor or outdoor applications such as golf facilities and driving ranges. Highly durable with a low face weight and a natural aesthetic are among the many benefits when choosing this golf grass variety.

SKU	RANGE
Grass Zone Yarn/Color	PE / Field Green / Lime / White
Grass Zone Denier	10,000 / 1
Thatch Zone Yarn/Color	-
Thatch Zone Denier	-
Grass Zone Yarn Shape	Slit Film
Finished Pile Height	1"
Finished Pile Weight	33 oz.
Backing	15 / 18 PP 2-Part / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	61 oz.
Tuft Bind	> 8 lbs.
Permeability	> 100 inches per / SY
Features	EnviroLoc+™ Deluster UV Stabilizers
Test Data	-

-  10 Year Warranty
-  UV Protection
-  Deluster



3 Colors available
Field Green | Lime | White
Ask about Custom Colors



ASK FOR A...



RECOMMENDED USES



Primary Yarn Polymer	Polyethylene	Primary Backing	15/18 PP 2-Part
Yarn Cross Section	Slit Film	Coating Type	22 oz. EnviroLoc+
Standard Color	3 colors available	PE Yarn Denier / Ends	10,000 / 1
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	-
Second Yarn Polymer Thatch	-	Warranty Period	10 Years
Secondary Yarn Color	-		

Finish Fabric	English System		ASTM Test
	Nominal Specification	Value	Units
Pile Height (Nominal)	1	inches	D-5823
Face Weight	33	oz/yd ²	D-5848
Total Fabric Weight	61	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	10,000	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	> 100	in/hr	D-1551
Fabric Width	15	ft	-